


## TF-QB1



Vertinimas: Kol kas vertinim? n?ra

### Kaina

?prastin? kaina 157,30 €

Kaina su nuolaida 130,00 €

Pardavimo kaina 157,30 €

Kaina be PVM 130,00 €

Nuolaida

PVM 27,30 €

[Užduoti klausim? apie š? produkt?](#)

### Aprašymas

Control card	<b>TF-QB1</b>
Function	Arbitrary partition, Multi partition arbitrary super position, Program background animation, Streamer word, Text strokes, Smart scan, support cross screen, video/video no need transcoding) audio, picture
Interface	100M Ethernet+ Gigabit Ethernet + U-disk
Cascade mode	support cascade connected with receiving card, to improve refresh rate( receiving card TF-RB01/TF-RB02)
Pixel range	Full color 512x192-1024x60 (Height max7612Width max71024)
LAN port Communication	Control card default IP:192.168.1.252, support network automatically search10M/100M/1000Madaptive, support U-disk updated program.
U-disk function	Support U-disk updating program, adjusting brightness, modify the parameters, support the programs(which is stored in U-disk) playing directly.
Hub board	2 x 50 Pin(height max support 10 pcs HUB75)
Scan type	support 1-32 scan type, support "smart scan".
Memory	4GB?Support U-disk memory expansion?
Program QTY	Maximum support 200 programs, support 16 partitions play at the same time, Partitions can overlap, each widow support 200 texts
Effect	45 kinds of different actions.
Colorful border	support a lot Colorful borders, support picture user-defined borders.
Content type	Video, audio, Text, flash, picture, animation, timing, count down, count up, clock, Temperature, humidity, weather.
Play type	program support playing by turns, by timing, by date, by week, by time quantum.
Time display	Clock, time, time with seconds, support adjusting font size, can set time zone, support many different time zones play at the same time.
Communication	lan port communication, support U disk update program.
Brightness adjust	16 levels brightness, support Manual adjustment of brightness, support 6 period timing adjust brightness, Auto adjust brightness.
Screen switch	manual screen switch, support 4 period timing screen switch.
Test Key	test key on board, can Switch test mode.
Electrical parameters	+5V DC(4.5V/75.5V)
Working temperature	-30??77??